

BELT PRESS EBP 650



Bruttopreis:
330 310 €

Nettopreis:
268 545 €

Belt press with pneumatic belt tensioner, automatic belt control, high pressure belt cleaner and optional brush cleaning system for the belt. The mash is applied to the belt in a uniform layer by the adjustable metering box, at the end of the pressing sequence the pomace is removed from the belt by a scraper. In combination with our WALC and WAR65 washing systems, the level of the metering box is automatically supervised and controlled.

Processable materials

Apples, Pears, Quince, Blueberries, Beetroot, Carrots, Manioc, Vegetables.

This represents just an example, based on different materials and a selection of fruit processed in practice.

Technical data

Height pomace ejector	840 mm
Height waste water drain	210 mm
Height juice outlet	400 mm
Connection for juice outlet	2
Connection for waste water	ø 75 mm
Water consumption for cleaning	3 l/min
Contact time	1,9 - 3,8 min
Belt speed	0,9 - 1,8 m/min
Juice yield	75 %



Material	1.4301 / AISI 304
Weight	1 060 kg
Conveyor height	0 - 50 (stufenlos) mm
Conveyor width	450 mm
Strip length	7 200 mm
Belt width	650 mm
Discharge height	1 460 mm
Height	1 460 mm
Width	1 460 mm
Length	2 540 mm
Electrical protection	16 A
Connected load	400V 50Hz (dreiphasig)
Motor rating	Antriebsmotor 0,55 (0,75) Reinigungsmotor 0,12 (0,16) kW (PS)
Nominal rating kg/h	1 500 kg/h

GERÄTESPEZIFIKATIONEN

Gewicht: 1060 kg

Produktionsland: Austria

Herstellergarantie: 1 rok

Elektrischer Anschluss:

Nennleistung kg / h: 1500 kg owoców/h

Saftausbeute:

Abmessungen in cm (B x H x L): 146,3 x 146 x 254

Material: 1.4301 / AISI 304

Wysokość przyjęcia owoców: 146 cm





GALERIE

