

BELT PRESS EBP580



Bruttopreis:
207 260 €

Nettopreis:
168 504 €

Belt press with pneumatic belt tensioner, automatic belt control, high pressure belt cleaner and optional brush cleaning system for the belt. The mash is applied to the belt in a uniform layer by the adjustable metering box, at the end of the pressing sequence the pomace is removed from the belt by a scraper. In combination with our WALC and WAR65 washing systems, the level of the metering box is automatically supervised and controlled.

Processable materials

Apples, Pears, Quince, Carrots, Beetroot, Manioc, Vegetables. This represents just an example, based on different materials and a selection of fruit processed in practice.

Technical data

Height pomace ejector	745 mm
Height waste water drain	86 mm
Height juice outlet	305 mm
Connection for juice outlet	1 ½ "
Connection for waste water	DN75
Water consumption for cleaning	3 l/min
Belt speed	2,1 - 5,5 (stufenlos) m/min
Juice yield	75 %
Material	1.4301 / AISI 304

Weight	665 kg
Conveyor width	240 - 460 mm
Belt width	580 mm
Discharge height	1 290 mm
Height	1 290 mm
Width	1 270 mm
Length	2 145 mm
Electrical protection	16 A
Connected load	400V 50Hz (dreiphasig)
Motor rating	Antriebsmotor 0,75 (1,02) Reinigungsmotor 0,37 (0,5) kW (PS)
Nominal rating kg/h	up to 1 000 kg/h

GERÄTESPEZIFIKATIONEN

Gewicht: 665 kg

Produktionsland: Austria

Herstellergarantie: 2 lata

Elektrischer Anschluss:

Nennleistung kg / h: 1000 kg/h

Saftausbeute:

Abmessungen in cm (B x H x L): 127 x 129 x 215

Material: 1.4301 / AISI 304

Wysokość przyjęcia owoców: 130 cm



GALERIE

