



## SINGLE FERMENTATION CONTROLLER MOUNTED DIRECTLY ON THE TANK, NANO TANK



**Bruttopreis:**  
**971 €**

**Nettopreis:**  
**789 €**

The latest single unit fermentation controller for one tank, with a clear display of actual and target temperature. The unit can be easily mounted into a thermowell on the tank because of the stainless steel sleeve on its back. The Nano Tank can be centrally operated with the Nano Terminal, which significantly increases functional options. For easy and professional wiring, we recommend the Nano Box.

- With thermowell, permanent installation directly on the tank
- Actual and target display
- Junction cable ca. 6m with cable strand
- Stainless steel sleeve 7 mm x 240 mm
- Housing polycarbonat
- Central operation with Nano Terminal via data line
- Display: Target and actual temperature
- Accuracy: +/- 0.5°
- Resolution: +/- 0.1°
- Range: -9.9°...+99.9°C
- Controller system: PID





- Operational modes: Cooling, warming
- Rear side: Sleeve: circa. 7 x 240mm
- Casing: Plastic, PC (Polycarbonate) with GF
- Operating temperature: -10 to +40°C
- Voltage: 24V AC +/- 10%
- Connecting cable: 6 Meters (braided wire)
- Dimensions: WxHxD: 100x120x330 mm
- International protection code: IP65

