



TWIN BELT PRESS ZBP660



Twin belt press with pneumatic belt tensioner, automatic belt control, high pressure belt cleaner and brush cleaning system for the belt. The mash is applied to the belt in a uniform layer by the adjustable metering box, at the end of the pressing sequence the pomace is removed from the belt by a scraper. In combination with our WAR65 washing system, the level of the metering box is automatically supervised and controlled.

Processable materials

Apples, Pears, Quince, Blueberries, Beetroot, Carrots, Vegetables, Manioc. This represents just an example, based on different materials and a selection of fruit processed in practice.

Technical data

| | |
|-----------------------------|---|
| Scope of supply | HD-Reiniger, Kompressor, inkl. Bürstenwalzen angetrieben (oben und unten) |
| Height pomace ejector | 810 mm |
| Height waste water drain | 50 mm |
| Height juice outlet | 130 mm |
| Connection for juice outlet | DN25 |
| Connection for waste water | ø 75 mm |



| | |
|--------------------------------|------------------------|
| Water consumption for cleaning | 10 l/min |
| Contact time | 1,4 - 4,2 min |
| Belt speed | 1,2 - 4,5 m/min |
| Juice yield | bis zu 80 % |
| Material | 1.4301 / AISI 304 |
| Weight | 2 200 kg |
| Conveyor height | 10 - 40 mm |
| Conveyor width | 220 - 440 mm |
| Belt width | 660 mm |
| Discharge height | 1 430 mm |
| Height | 2 110 mm |
| Width | 1 730 mm |
| Length | 3 720 mm |
| Electrical protection | 16 A |
| Connected load | 400V 50Hz (dreiphasig) |
| Motor rating | 3,5 kW (PS) |
| Nominal rating kg/h | up to 3 000 kg/h |

GERÄTESPEZIFIKATIONEN

Produktionsland: **Austria**

Herstellergarantie: **1 rok**

Elektrischer Anschluss:

Nennleistung kg / h: **3000 kg/h**

Saftausbeute:

Material: **1.4301 / AISI 304**



GALERIE

